

Introducing the all new **JXT** series
**Power, Performance
and Durability**

JX 55T & JX 75T

The Case IH brand inherits a legacy of competent leadership from the most respected agricultural equipment companies and brands like Case and International Harvester, to name a few. The JXT series from Case IH combines power and durability to deliver unmatched performance in demanding applications and an efficiency based on heavy-duty components to ensure a long life with the least downtime. Engineering that delivers a reliable and durable performance is what you can expect from Case IH.



Technical Specification

MODEL	JX 55T	JX 75T
ENGINE No. of cylinders / Aspiration Displacement (Capacity cm ³) Power (kW / hp) @ 2500 rpm Max. torque (Nm @ rpm) Air Cleaner	IVECO Series 8000 3 CYL NA 2931 40 / 55 184 Nm @ 1500 rpm Oil Bath with Pre Cleaner	IVECO Series 8000 4 CYL NA 3908 55 / 75 242 Nm @ 1500 rpm Oil Bath with Pre Cleaner
TRANSMISSION Transmission clutch Total number of speeds Gearbox features Optional Speeds (with creeper)	Single 8 forward, 2 reverse Partially constant mesh and partially synchromesh 12 forward, 3 reverse	Double 8 forward, 2 reverse Constant mesh (optional partial synchromesh) 12 forward, 3 reverse
STEERING	Power	Power
POWER TAKE OFF PTO features PTO speed (rpm)	Fully independent 540	Fully independent 540
HYDRAULICS Type of Hydraulic Pump Max. flow output (l/min) / Max pressure (BAR) Control features (Position, Draft etc) Draft Control Max. load capability at ball end W/horizon. links (kgs)	Gear Type 32 / 190 Position / Draft / Mix / Lift O Matic Top link Std. 1525	Gear Type 32 / 190 Position / Draft / Mix / Lift O Matic Top link Std. 1525 / opt. 2100
FUEL TANK CAPACITY	62	62
REAR AXLE Wheel base 2WD / 4WD (mm) Overall Width Overall Length Turning Radius with brake- 2WD/4WD Turning Radius without brake- 2WD/4WD Ground clearance under front axle 2WD / 4WD (mm) Ground clearance under rear axle (mm) Height to the top of exhaust 2WD / 4WD Type Size 2WD Front/Back Type Size 4WD Front/Back	2050 / 2010 1925 3550 3205 / 4200 3500 / 5100 500 / 380 530 2200 / 2210 7.5 - 16 / 16.9 - 28 9.5 - 24 / 16.9 - 28	2200 / 2160 1990 3500 3275 / 4200 3705 / 5260 500 / 410 555 2375 / 2385 7.50-16 / 16.9-30 11.2-24/16.9-30
TOTAL WEIGHT 2WD/4WD (KG)	2150/2275	2370/2495

Optional: • Rops • Canopy • Front & Rear Weights • I2+3 UG • Auxiliary Valve • Ground Speed PTO • 2100 kg Lift Capacity • Single Clutch

*Optional



IVECO ENGINE
With rotary FIP - Powerful, reliable and fuel efficient.



OIL IMMERSER MULTI DISC BRAKES
Less maintenance, Long Lasting, and Powerful Brakes



CONSTANTMESH - SIDE SHIFT GEAR BOX
Long lasting and makes gear shifting easier



LIFT-O-MATIC
With Height Limiter - Increased productivity and higher efficiency.



4WD* More Traction - Better coverage, increased efficiency for tough jobs.



OPERATOR COMFORT
Comfortable environment for operator - Increased productivity.

Authorized Dealer

Note: Since product upgradation is a continuous process, specifications and details provided are subject to change without prior intimation. The accessories/implements shown here are not a part of standard equipment. New Holland does not promote or take responsibility for any equipment not manufactured by the company.

New Holland Fiat (India) Pvt. Ltd.