

Introducing the all new **JXT** series
**Power, Performance
and Durability**

JX 40T & JX 45T

The Case IH brand inherits a legacy of competent leadership from the most respected agricultural equipment companies and brands like Case and International Harvester, to name a few. The JXT series from Case IH combines power and durability to deliver unmatched performance in demanding applications and an efficiency based on heavy-duty components to ensure a long life with the least downtime. Engineering that delivers a reliable and durable performance is what you can expect from Case IH.



Technical Specification

MODEL	DETAIL	JX 40T	JX 45T
ENGINE	Type	Trem 3A, 4 Stoke, 3 cylinder, Water cooled, Inline pump.	
	Rated RPM	2000	2250
	Air Cleaner	Oil Bath with Pre Cleaner	
ENGINE HP RANGE		45 Hp Category	50 Hp Category
TRANSMISSION	Clutch	Single	
	Standard Transmission	8 forward + 2 reverse (constantmesh)	
	Optional Transmission	8+8 synchro shuttle	
BRAKES	Type	Oil Immersed Multi Disc Brakes	
HYDRAULICS	Lift Capacity	1100 kg	
STEERING	Type	Manual	
PTO	RPM	540	
TYRES	Front	6.0 x 16	
	Rear	13.6 x 28	13.6x28/ 14.9x28
FUEL TANK CAPACITY		62 liters	
DIMENSIONS AND WEIGHT	Total Weight (kg)	1810	2050
	Wheel Base (mm)	1920	1965
	Ground Clearance (mm)	380	382
	Turning Radius with Brakes (mm)	2930	2980



OIL IMMERSED MULTI DISC BRAKES
Less maintenance, Long Lasting, and Powerful Brakes.



LIFT-O-MATIC
Button operated hydraulic makes it easier to lift and put down implement and maintains uniform depth.



CLUTCH WITH BIGGER DIAPHRAGM
Less maintenance, uses less energy and gives you more comfort



PLANETARY REDUCTION
Capacity to pull more load, more durability, and better pick-up



COMPANY FITTED ADJUSTABLE TOW-HOOK
Capacity to carry more load and easy adjustment of trolley



BEST IN CLASS OPERATOR COMFORT



CONSTANTMESH - SIDE SHIFT GEAR BOX
Long lasting and makes gear shifting easier

Technical Features

- Standard:** • Diaphragm Type Clutch • Spin-on Dual Filters • Fiber Fuel Tank • Lift -O-Matic • Oil Immersed Brakes
• Planetary Reduction • Side Shift Constantmesh gear box • Rear Ballast • Front Weight Carrier • Reverse PTO & Ground PTO
• Digital Hour Meter • Neutral Safety Switch • Sliding Seat • Bottle Holder • Mobile Charger • Tow Hook
- Optional:** • Power Steering • Double Clutch • 8+8 Synchro Shuttle • 4WD • Auxiliary Valve • 540-E • 1500 kg Lift Capacity

Authorised Dealer

Note: Since product upgradation is a continuous process, specifications and details provided are subject to change without prior intimation. The accessories/implements shown here are not a part of standard equipment. New Holland does not promote or take responsibility for any equipment not manufactured by the company.